



SC UNO



SC UNO

Stationary 1-pump high pressure washer

Innovative hard foam cabinet

- The newly developed hard foam cabinet reduces noise level and has been approved for the food industry.
- Built on solid powder-coated steel frame.
- New simple control panel.

Flexibility

- High reconfigurability, customisation with optional equipment to meet specific needs.
- Cold or hot water inlet for maximum cleaning efficiency.
- Ideally suited for use in agriculture, garages, construction, food and pharmaceutical.

Serviceability

- Low pump oil safety function and warning light (exc. 5 ML variant).
- Hour counter and service warning light (exc. 5 ML variant).
- Easy access to motor pump and parts; saving time on maintenance.

Customised for lower TCO

- Choose a basic or more feature packed model to achieve low Total Cost of Ownership.
- Extra optional features to meet your specific needs.
- Optional add-ons to fulfil EU norm 1717: Water Break Tank.

Quality to perform

- Intelligent start-stop function for motor pump, reducing wear on pump elements.
- Powered by 1450rpm high efficiency motor (50Hz).
- Cleaning efficiency is maximised by the 3-piston and 4-piston long-life motor pumps with brass pump heads.
- Ideal for medium and heavy duty cleaning challenges.
- NA5.2 pump on 5M and 5M L variants, and NA6 pump on 6P and C3 on 7P variants.




TECHNICAL DATA	SC UNO 5M-200/1050 L	SC UNO 5M-200/1050	SC UNO 6P-170/1610	SC UNO 7P-180/1200
Pump pressure (bar/MPa)	200/20	200/20	170/17	180/18
Cleaning impact (kg/force)	5.5	5.5	7.9	5.9
Water flow Qmax/Qiec (l/h)	1050/960	1050/960	1610/1500	1200/1080
Max. inlet temperature - Direct pressure (°C)	60	60	70	80
Max. inlet temperature - Water Break Tank (°C)	40	40	50	70
Pump (RPM)	1450	1450	1450	1450
Dimensions L x W x H (mm)	355x860x560	355x860x560	355x860x560	355x860x560
Weight (kg)	74	74	84	81
Power consumption (kW)	6.1	6.1	8.8	6.7
Voltage/phase/frequency/current (V~/Hz/A)	400/3/50/11.4	400/3/50/11.4	400/3/50/16.0	400/3/50/12.0
El cable (m)	5	5	5	5
Suction height dry / wet (m)	1 / 2.5	1 / 2.5	1 / 2.5	1 / 2.5
Nozzle size	.0500	.0500	.0900	.0640
FEATURES				
Pistons / number of pistons	Ceramic / 3	Ceramic / 3	Ceramic / 4	Ceramic / 4
Automatic start/stop	●	●	●	●
Service warning light		●	●	●
Hour counter		●	●	●
STANDARD EQUIPMENT				
HP hose	10 m (DN8)	10 m (DN8)	10 m (DN10)	10 m (DN10)
Ergo 2000 incl. swivel	106403122	106403122	106403122	106403122
Ergo coupling	101119496	101119496	101119496	101119496
Water inlet coupling	1602945	1602945	1602945	1602945
Tornado Plus lance	106403010	106403010	106403010	106403010
Tornado Plus nozzle	101119743	101119743	101119752	101119745
ITEM NO.	107340510	107340512	107340521	107340541

NEW CABINET CONCEPT



Innovative hard foam cabinet. Easy to remove, robust, lightweight and noise reducing. Also approved for the food industry.

EASY MAINTENANCE



Cabinet can be removed quickly for direct access to the motor pump.

Optional Accessories (see product catalogue for further accessories)



External Water Break Tank
For use with machines up to 40ltr/min.
Required to fulfill EU norm 1717:



Accessory storage kit
For lances, hose, gun and foam sprayer.



Detergent
Use of detergents makes cleaning quicker and easier. The chemical compounds breakdown and bind the dirt particles.

Distributed by:

Sharpe Maintenance Services Ltd
Tel: 0116 254 6049
Email: sms@sharpemaintenance.co.uk
www.sharpemaintenance.co.uk

